

Inductive sensors Multinorm

41.5 x 41.5 x 120



Rated operating distance	
Mounting	flush /non-flush
Switching functions	
	Model description
Normally-open (NO)	Wiring diagram (page/pos.)
Stock status: Ex stock/Built to order	
	Model description
Normally-closed (NC)	Wiring diagram (page/pos.)
Stock status: Ex stock/Built to order	
	Model description
Normally-closed/open (NC/NO)	Wiring diagram (page/pos.)
Stock status: Ex stock/Built to order	
	Model description
Complementary	Wiring diagram (page/pos.)
Stock status: Ex stock/Built to order	

Electrical data	
Voltage range	min./max.
Output current	min./max.
Switching frequency	max.
Short-circuit protection	
LED: yellow = switched / green = power	
Sensitivity adjustment	

Mechanical data	
Temperature range	min./max.
Protection type	
Housing material	
Termination	cable 2 m/6.5 ft mm ² plug (page)
Accessories (page/Pos.)	

Dimension diagrams

All dimensions in mm (inch)

41.5 x 41.5 x 120

15 mm (0.59")

●/-	●/-	-
NPN	PNP	AC
Model description		
Part number		
KIB-N44DP/ 015-KLS		
650.2054.001		
263/7		
●/-	-	-

KIB-N44NP/ 015-KLS	KIB-N44PP/ 015-KLS	KIB-N44AP/ 015-LS
650.2354.011	650.2954.011	650.3554.009
263/6	263/3	265/6
-/●	-/●	●/-

41.5 x 41.5 x 120



20 mm (0.78")

-/●	-/●	-
NPN	PNP	AC
Model description		
Part number		
KIN-N44DP/ 020-KLS		
650.2054.002		
263/7		
●/-	-	-

KIN-N44NP/ 020-KLS	KIN-N44PP/ 020-KLS	KIN-N44AP/ 020-LS
650.2354.012	650.2954.012	650.3554.010
263/6	263/3	265/6
-/●	●/-	●/-

10-60 V	10-60 V	20-250 V	10-60 V	10-60 V	20-250 V
-/400 mA	-/400 mA	4/500 mA	-/400 mA	-/400 mA	4/500 mA
100 Hz	100 Hz	15 Hz	50 Hz	50 Hz	15 Hz
●	●	-	●	●	-
●/●	●/●	●/●	●/●	●/●	●/●

-25 °C/+70 °C	-25 °C/+70 °C	-25 °C/+70 °C	-25 °C/+70 °C	-25 °C/+70 °C	-25 °C/+70 °C
-13 °F/+158 °F	-13 °F/+158 °F	-13 °F/+158 °F	-13 °F/+158 °F	-13 °F/+158 °F	-13 °F/+158 °F
IP 65/NEMA 12	IP 65/NEMA 12	IP 65/NEMA 12	IP 65/NEMA 12	IP 65/NEMA 12	IP 65/NEMA 12
PA 6.6	PA 6.6	PA 6.6	PA 6.6	PA 6.6	PA 6.6





41.5 x 41.5 x 120 extended sensing distance

20 mm (0.78")

●/-	●/-	-
NPN	PNP	AC
		-
KIB-N44DP/ 020-KLSE 650.2054.004 263/7 ●/-		-

41.5 x 41.5 x 120 extended sensing distance

40 mm (1.57")

-/●	-/●	-
NPN	PNP	AC
		-
KIN-N44DP/ 040-KLSE 650.2054.005 263/7 ●/-		-

-	-	KIB-N44AP/ 020-LSE 650.3554.001 265/6 ●/-	-	-	KIN-N44AP/ 040-LSE 650.3554.002 265/6 -/●
---	---	--	---	---	--

-	10-60 V	20-250 V	-	10-60 V	20-250 V
-	-400 mA	-500 mA	-	-400 mA	-500 mA
-	50 Hz	15 Hz	-	50 Hz	15 Hz
-	●	-	-	●	-
-	●/●	●/●	-	●/-	●/●

-	-25 °C/+70 °C	-25 °C/+70 °C	-	-25 °C/+70 °C	-25 °C/+70 °C
-	-13 °F/+158 °F	-13 °F/+158 °F	-	-13 °F/+158 °F	-13 °F/+158 °F
-	IP 65/NEMA 12	IP 65/NEMA 12	-	IP 65/NEMA 12	IP 65/NEMA 12
-	PA 6.6	PA 6.6	-	PA 6.6	PA 6.6

